EXS210147-01

488nm SLED Butterfly with PMF

Revision: 1.1
Date: 08-07-2024
Confidentiality: None

Prepared by: Marco Rossetti
(R&D Manager visibles)

Checked by: Jan Mostel
(Quality Manager)

Approved by: Marcus Duelk
(VP of R&D)

Authorized by: Stephane Chappuis
(VP of operations)

CONTENTS

1. SCOPE 3
1.1 PURPOSE 3
1.2 RESPONSIBILITY 3

2. REFERENCE DOCUMENT 3

3. ELECTRO-OPTICAL PERFORMANCE (T_{SLED} = 25°C) 3

4. ABSOLUTE MAXIMUM RATINGS 4

5. SCREENING 4

6. PACKAGE DIMENSIONS [MM] 5

7. FIBRE AND CONNECTOR 5

8. IMPORTANT NOTES 6

9. ORDERING INFORMATION 6
9.1 TECHNICAL DESCRIPTION 6

10. REVISION HISTORY 7

1. SCOPE

1.1 PURPOSE

The purpose of this document is to specify the electro-optical performance and dimensions of superluminescent light emitting diode (SLED).

1.2 RESPONSIBILITY

EXALOS is responsible for establishing, implementing and maintaining this procedure. The Quality representative shall ensure that a timely Engineering Change Notice (ECN) is issued in accordance with EXALOS procedure for any changes.

2. REFERENCE DOCUMENT

- EXS-WI-0001 Visual Inspection Criteria SLED Chip on Submount Procedure
- MIL STD 883 C method.
- Bellcore GR-468-CORE.

3. ELECTRO-OPTICAL PERFORMANCE (T_{SLED} = 25°C)

Parameter	Symbol	Cond.	Min	Typ	Max	Unit
Power in SMF	P_{op}				5	mW
Operating Current	I_{op}	$P_{op,\ max}$	350		500	mA
Operating Voltage	V_{op}	$P_{op,\ max}$		6.3	7	V
Center Wavelength	λ_c	$P_{op,\ max}$	483	488	493	nm
Bandwidth FWHM		$P_{op,\ max}$	3.5	5		nm
Spectral ripple [RB=0.05nm]		$P_{op,\ max}$		0.1	0.3	dB
Polarization Extinction Ratio	PER			12		dB
Polarization Orientation			electric field along slow axis			

4. ABSOLUTE MAXIMUM RATINGS

Stresses beyond the absolute maximum ratings may cause permanent damage to the device. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

Parameter	Symbol	Cond.	Min	Max	Unit
Forward current	I_F			500	mA
Reverse voltage	V_R			-2	V
Forward voltage	V_F	$I_{F,max}$		7.5	V
Storage temperature	T_{stg}		-40	85	°C
Operating temperature	T_{op}	$I_{F,max}$	-20	50	°C
Storage humidity		<30°C >30°C	5	95 85	% r.h. % r.h.
Thermoelectric cooler voltage	V_{tec}			5.0	V
Thermoelectric cooler current	I_{tec}			5.0	A
Thermistor Resistance	R_{th}	25°C	10		KΩ
Thermistor constant	B		3892		K
Lead soldering temperature				260	°C
Lead soldering duration				10	s
ESD		human b.m		500	V

5. SCREENING

The 488nm SLED Module meets all operating conditions specified in the table of section 3 (Electro-Optical Performance) after being subjected to the following screening tests.

Test Item	Test Conditions	Reference
Seal	Fine: Condition A1 Gross: Condition C	MIL-STD-883, Method 1014 Temperature max 85°C
Temperature Cycling	-40°C to +85°C, ramp rate >= 5°C/min 10 cycles	MIL-STD-883, Method 1010

3rd Angle projection

6. PACKAGE DIMENSIONS [mm]

Tolerances : .X ± 0.25 mm



.XX ± 0.05 mm

Butterfly Package			
Pin	**Function**	**Pin**	**Function**
1	**TEC (+)**	**8**	**NC**
2	**THERMISTOR**	**9**	**NC**
3	**NC**	**10**	**SLED ANODE (+)**
4	**NC**	**11**	**SLED CATHODE (-)**
5	**THERMISTOR**	**12**	**NC**
6	**NC**	**13**	**CASE GROUND**
7	**NC**	**14**	**TEC (-)**

7. FIBRE AND CONNECTOR

Part	**Description**
Polarization-Maintaining SM Fibre	PM 3.3/125 μm Nufern PM-S405-XP
Loose tube secondary coating	900 μm
Fiber pigtail length [min]	1 m
Optical connector	FC/APC*, PMF Key aligned to slow axis +/- 5° tolerance

*Narrow Key (2.0mm)

8. IMPORTANT NOTES

1. Avoid electrostatic discharges, which may destroy the SLED.
2. Never use the SLED module without heat sinking.
3. Adequate eye protection against laser radiation should be used while handling and operating the module.
4. EXALOS declines any responsibility if the device is used in applications where human life may be endangered.
5. Back reflections may influence the output power and spectral characteristics of the SLED. The use of optical isolators and/or angled connectors is recommended. Back reflections of less than -30dB are recommended.

9. ORDERING INFORMATION

Please use the following **part number** to order product from EXALOS:

E	X	S	2	1	0	1	4	7	–	0	1

9.1 TECHNICAL DESCRIPTION



10. REVISION HISTORY

Revision History				
Rev.	**Description**	**ECN**	**Date**	**Released**
1.0	First revision	EXS-EC-01421	16.05.2022	Rossetti
1.1	Minor revision. Modified operating conditions (Pmax-Irange)	EXS-EC-01634	08.07.2022	Rossetti