EXS210181-02

SLED Butterfly λ=840nm

Revision: 2.0
Date: 21-01-2025
Confidentiality: None

Prepared by: Alessio Poretti
(Software, Integration and Test Engineer)

Checked by: Jean Dahdah
(Product Engineer Manager)

Approved by: Jan Möstel
(Quality Manager)

Authorized by: Stephane Chappuis
(VP Operations)

CONTENTS

1. SCOPE 3
1.1 PURPOSE 3
1.2 RESPONSIBILITY 3
2. REFERENCE DOCUMENT 3
3. ELECTRO-OPTICAL PERFORMANCE (T_{SLED} = 25°C) 3
4. ABSOLUTE MAXIMUM RATINGS 4
5. SCREENING 4
6. PACKAGE DIMENSIONS [MM] 5
7. FIBRE AND CONNECTOR 5
8. IMPORTANT NOTES 6
9. ORDERING INFORMATION 6
9.1 TECHNICAL DESCRIPTION 6
10. REVISION HISTORY 7

1. SCOPE

1.1 PURPOSE

The purpose of this document is to specify the electro-optical performance and dimensions of superluminescent light emitting diode (SLED).

1.2 RESPONSIBILITY

EXALOS is responsible for establishing, implementing and maintaining this procedure. The Quality representative shall ensure that a timely Engineering Change Notice (ECN) is issued in accordance with EXALOS procedure for any changes.

2. REFERENCE DOCUMENT

- EXS-WI-0001 Visual Inspection Criteria SLED Chip on Submount Procedure
- MIL STD 883 C method.
- Bellcore GR-468-CORE.

3. ELECTRO-OPTICAL PERFORMANCE (T_{SLED} = 25°C)

Parameter	Symbol	Cond.	Min	Typ	Max	Unit
Operating Current	I_{op}				230	mA
Power in SMF	P_o	$I_{op,\ max}$	25	30		mW
Center Wavelength	λ_c	$I_{op,\ max}$	825	835	845	nm
Bandwidth FWHM		$I_{op,\ max}$	20	25		nm
Secondary coherence peak suppression*	SPSR	Imaging depth in air† 0 - 15mm	26			dB
Monitor PD Current‡	I_{MPD}	$I_{op,\ max}$	100			µA
Monitor PD bias voltage			0		-12	V

* SPSR is the difference in dB (on a 10-log scale) of the DC peak and the amplitude of the secondary peak of the coherence function. The coherence function is calculated through a Fourier transform of the optical spectrum, measured from 770 nm to 920 nm (150 nm span) with a sampling bandwidth of max. 20 pm (optical resolution) and an oversampling factor of at least 2.0 (max. numerical resolution 10 pm), and resampled with equidistant steps in the frequency domain (k-space).

† Imaging depth equals twice the optical path length difference (OPD) in an interferometer.

‡ Measurement conditions:

- $I_{op} = I_{op}$ Max
- Monitor PD bias voltage: 0 Volts

Input resistance of the Monitor PD current measurement circuit 10 Ohm

4. ABSOLUTE MAXIMUM RATINGS

Stresses beyond the absolute maximum ratings may cause permanent damage to the device.
Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

Parameter	Symbol	Cond.	Min	Max	Unit
Forward current	I_F			300	mA
Reverse voltage	V_R			-2	V
Forward voltage	V_F	$I_{F,max}$		2.5	V
Storage temperature	T_{stg}		-40	85	°C
Operating temperature	T_{op}	$I_{F,max}$	-20	65	°C
Storage humidity		<30°C >30°C	5	95 85	% r.h. % r.h.
Thermoelectric cooler voltage	V_{tec}	**		4.0	V
Thermoelectric cooler current	I_{tec}	**		1.8	A
Thermistor Resistance	R_{th}	25°C	10		KΩ
Thermistor constant	B		3892		K
Lead soldering temperature				260	°C
Lead soldering duration				10	s
ESD		human b.m		500	V

** Performance values with hot side temperatures 50°C

5. SCREENING

The produced 840nm SLED Module is required to meet all operating conditions specified in Table 3, Electro-Optical Performance Specifications after being subjected to the following screening tests.

Test Item	Test Conditions	Reference
Seal	Fine: Condition A1 Gross: Condition C	MIL-STD-883, Method 1014 Temperature max 85°C
Temperature Cycling	-40°C to +85°C, ramp rate >= 5°C/min 10 cycles	MIL-STD-883, Method 1010

3rd Angle projection

6. PACKAGE DIMENSIONS [mm]

Tolerances : .X ± 0.25 mm
.XX ± 0.05 mm



Butterfly Package			
Pin	**Function**	**Pin**	**Function**
1	TEC (+)	8	NC
2	THERMISTOR	9	NC
3	MONITOR DIODE ANODE	10	SLED ANODE (+)
4	MONITOR DIODE CATHODE	11	SLED CATHODE (-)
5	THERMISTOR	12	NC
6	NC	13	CASE GROUND
7	NC	14	TEC (-)

7. FIBRE AND CONNECTOR

Part	Description
SM Fibre	SM 5/125 Corning HI780
Loose tube secondary coating	900 μm
Fiber pigtail length [min]	1 m
Optical connector	FC/APC Narrow Key (2.0mm)

8. IMPORTANT NOTES

1. Avoid electrostatic discharges, which may destroy the SLED.
2. Never use the SLED module without heat sinking.
3. Adequate eye protection against laser radiation should be used while handling and operating the module.
4. EXALOS declines any responsibility if the device is used in applications where human life may be endangered.
5. Back reflections may influence the output power and spectral characteristics of the SLED. The use of optical isolators and/or angled connectors is recommended. Back reflections of less than -30dB are recommended.

9. ORDERING INFORMATION

Please use the following **part number** to order product from EXALOS:

E	X	S	2	1	0	1	8	1	–	0	2

9.1 TECHNICAL DESCRIPTION



10. REVISION HISTORY

Revision History				
Rev.	**Description**	**ECN**	**Date**	**Released**
1.0	Original version	EC-01590	18.12.2023	Rezzonico
2.0	Updated forward current consequent output power	EC-01701	21.01.2025	Poretti